

# Unicycle.com

## Mounting a brake using a Nimbus Brake Mount

The Nimbus Brake Mount is designed to fit underneath the saddle and secure the brake handle in a position where it can be activated by your hand while holding the saddle. Due to shipping constraints these are not normally installed during shipping.

### Instructions:

1. If the brake mount is already installed to saddle, remove using an allen key.
2. Loosen the mounting bolts on the brake handle.
3. Slip the handle over the tube of the brake mount and lightly tighten.
4. Next you need to check the position of the brake handle on the mount, it must be in a position that you can grip it and does not touch the ground when the unicycle is dropped.
  - a. Lightly mount the brake mount on the saddle.
  - b. If not already fitted, fit the saddle on the unicycle at your normal riding height.
  - c. Hold the unicycle so that it has the saddle with the handle on the ground. This will tell you if the handle is positioned so it does not touch the ground. Make sure there is at least 5mm between the end of the handle and the ground.
  - d. With the unicycle in front of you check if you can grab the brake handle effectively. Some prefer the handle twisted towards their dominant hand.
5. Once you are happy that the brake handle is correctly positioned, tighten up the bolts on the brake handle to hold it securely in position.
6. Remount the Nimbus Brake Mount securely to the saddle.
7. Securely clip the hose to the frame using the clips provided with the frame.

